

SOLAR MOBILE TWIN TOILET



HSE & CDM COMPLIANT

Anti-vandal robust & easy-to-use single axle mobile toilet unit - ideal for **Construction, Rail, Utility and Hire industries.**



Innovative, functional, environmentally efficient and cost effective.

The mobile **groundhog** anti-vandal twin toilet unit has an in-built effluent tank, so there is no need to hire separate effluent tanks saving you time and money.

Robust and incredibly efficient, this unit offers huge reductions in fuel usage, carbon emissions and service schedules.

Incorporating the latest environmental solar technology, the **groundhog** twin toilet unit is *ideal for the ever increasing demands of the construction, rail, utility and hire industry.*

INNOVATION THAT WORKS.



Powered by two roof mounted 425W solar panels



High level windows c/w security frame



Fully hot-dipped galvanised chassis



12V LED lighting with PIR



Warm wash set over large stainless steel sink



x2 Full flush toilets



16Amp appliance inlet in lockable box



Lowered & secured in 3 minutes



Easy manoeuvrability on site

KEY FEATURES at a glance

For full specification, please visit
www.groundhog.co.uk



Length	3000 mm
Length (including drawbar)	4299 mm
Height (on wheels)	2.9 m
Height (on ground)	2.5 m

Unladen Weight	1690 kg
Possible Gross Weight *Unit should be towed dry at all times	2490 kg*
Solar Panel x2	2 x 425 W

Inverter	375 W
Fresh Water Container	2 x 20 Litres
Fresh Water Tank	2 x 200 Litres
Under Floor Waste Tank	2 x 200 Litres



1 Toilet Area

Full Flush Toilet
Large Stainless Steel Sink C/W Warm Water Tap
Liquid soap dispenser
200 Litre Fresh Water Tank
200 Litre Under floor Waste Tank
Waste outlet

2 Toilet Area

Full Flush Toilet
Large Stainless Steel Sink C/W Warm Water Tap
Liquid soap dispenser
200 Litre Fresh Water Tank
200 Litre Under floor Waste Tank
Waste outlet

3 Lockable access area under worktop

12V Water Pump
240AH Battery
Hydraulic Power Pack
Solar Charge Regulator
375W Inverter
Battery Charger

Flooring

Recycled Non-Slip Flooring

Internal construction

Lined and Insulated in GRP, panels with block insulation inserts

External construction

Steel profiled panels to side walls and roof
Steel personnel doors to two separate areas (Toilet areas)
Single axle trailer
Low level lifting eyes
High level lifting eyes
Fork pockets
High level windows c/w security frame
16 Amp appliance inlet c/w lockable steel box
2 x 425 Watt Solar panels fitted to roof
Easy access wheel removal

Road lighting

12 Volt fixed lighting c/w number plate bracket

* Fully laden gross weight exceeds maximum towing capacity, unit should be transported to site prior to making site ready.