









Delivery of hot water

Comfortable, Compact and HSE compliant.

The **groundhog** mobile GP500 Part Eco is robust and easy to use and also offers a larger seating area, accommodating up to 12-14 people — ideal for flexible on-site applications.

The units provide pleasant and safe working environments, ideal for rental companies and contractors.

Easily towed, one man operation secured and manoeuvred on site, in less than 3 minutes. Its many safety features make it a high secure and money saving choice of welfare unit.

The **GP500 Part Eco** offers offers the legendary robustness and ease of use of the standard Groundhog Mobile welfare unit whilst offering a green environmental solution.



non-slip flooring



Warm water from an on-board 230V heating system



Welded bush for removable low level lifting eyes



Fully hot-dipped galvanised chassis



12V LED lighting with PIR



Fuel Active



230V 1kW air blown heater



12V sockets & USB port connections



e Lowered & secured in 3 minutes

KEY FEATURES at a glance

Length	5000 mm
Length (including drawbar)	6320 mm
Height (on wheels)	2.9 m
Height (on ground)	2.5 m

Generator	6 kVA	
Unladen Weight	2300 kg	
Possible Gross Weight	3000 kg*	
Solar Panel	Optional	

Fresh Water	20 Litres
Waste Water	20 Litres
Toilet Tank Size	280 Litres
Fuel Tank Size	58 Litres



1 Canteen Area
Table and bench seating for up to 12–14 people
12V LED lighting with PIR
230V 1kW air blown heater
Warm water supplied by a 230V on-board heating system
Large stainless steel sink c/w warm water tap
230V single 2Amp socket outlet for charging mobiles and laptops
Generator start panel c/w hour run meter
Fresh & waste water containers (20 Ltr cap each)
12V pump for water system
12V sockets and USBs
Carbon monoxide monitor and smoke alarm

Toilet Area Plastic recirculating toilet 12V LED lighting with PIR Forearm wash basin c/w warm water tap Warm water supplied by a 230V on-board heating system Generator/ Warm Room 12V LED lighting with PIR 240V tubular heater Access to fuel tank with separate fuel level Ventilation panel

Fuel tank runtime = approx. 25 hours

Fuel Active system

PART ECO Option from groundhog


The latest concept in 12V technology delivers power to the LED lighting and USB sockets without the need for the generator to be running, resulting in lower CO2 emissions and reduced generator runtime.

Part Eco units are fitted with 12V LED lighting complete with PIR sensors to automatically sense movement, turning lights on or off as required.


Situated in the canteen, toilet and generator room, this feature gives owners and end users savings by way of reduced fuel usage, reduction in generator servicing, longer generator life, fewer breakdowns and reduced noise pollution.


Featuring **BATTERY POWERED** LED lighting & USB sockets

















Mobile Units have obtained type approval with VCA



