HogPowerS98

9.8kVa Power

MGMK 9800-300

1500rpm water cooled diesel power unit



TECHNICAL SPECIFICATIONS
at a glance



Key Features & Benefits

✓ 9.8kVA 230V AC Aux Power	plug and play power to meet even the most demanding site applications
✓ Diesel engine - Kubota Stage V	robust and easy to use with world class performance
✓ Zanardi alternator	heavy duty with proven reliability
✓ HVO (Hydrotreated Vegetable Oil) fuel approved	suitable to run on diesel, HVO or a mixture of both fuels

Performance

Generator

Alternator Synchronous type	ZANARDI PE28 2VS/4
Single phase power (110V)	N/A
Single phase power (230V)	9.8kVA
Battery (not included)	12V 44 Ah
Frequency	50 Hz
Insulation class	H
Mechanical protection - IP	23
Noise level	79Lwa 54 dBa@7m
Litres per hour	2.5L
Co2e emissions per hour	6.4Kg

Engine

Engine make	Kubota
Engine type	D1105
Fuel	Diesel / HVO
N° cylinders	3
Power	13.7 HP
Engine speed	1500 rpm
Cooling	Water
Oil capacity	5.11L
Starting system	Electric / Remote
Fuel consumption	265 gr/kwh

Dimensions & weights

Length (mm)	1100
Width (mm)	790
Height (mm)	1470
Dry weight - no fuel (Kg)	536
Wet weight - full fuel (Kg)	TBA

Application

Welfare units

Fusion Pulse Range	Mobile	GPO660
	Static	SW6100
		SWO7600
		SWO7600FF
		SWO9700

Standard Range	Static	SW6100D
		SWO7600D

TEL: 01639 641166
www.groundhog.co.uk

Mobile Units have obtained type approval with **VCA**